NSN 5935-00-564-4326

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-564-4326 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.009 inches **Overall Height:** 1.703 inches **Overall Width:** 1.703 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.142 inches and 0.157 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 1.375 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.375 inches **Distance From Mounting Shoulder To Front Face:** Between 0.442 inches and 0.447 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 24-61 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin Thready Qty Per Inch (tpi): 18

Thread Size:

1.408 inches

NSN 5935-00-564-4326

Fiig: A039b0

Electrical Receptacle Connector - Page 2 of 2



Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Nickel
Included Contact Quantity:
61 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.061 gold grains, troy and 0.061 silver grains, troy
Precious Material:
Gold and silver
Test Data Document:
81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Uns
Specification Data:
81349-mil-c-38999 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No