Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-565-2694

Thread Class:

2a and 2b

Thread Direction:

Left-hand and right-hand

Body Style:

Straight shape, internal coupling

Overall Length:

1.735 inches

Overall Diameter:

1.551 inches

Environmental Protection:

Heat resistant and cold resistant and shock proof and vibration proof

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1 Contact Position Arrangement Style:

20-27 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

22.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

Polarization Method:

Key, multiple key groove

Insert Position In Deg:

110.0

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling ring

Thready Qty Per Inch (tpi):

18 and 10

Thread Size:

1.125 inches and 1.250 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

N/a

No

Electrical Plug Connector - Page 2 of 2



Contact Surface Treatment: Silver single mating end single contact grouping **Insert Material:** Rubber single mating end **Contact Surface Treatment Specification:** Qq-s-765 federal specification single treatment response single mating end single contact grouping **Terminal Type:** Solder well single mating end single contact grouping **Contact Material Specification:** Sae ca147 assn standard single material response single mating end single contact grouping Shell Material: Steel comp 302 **Shell Surface Treatment:** Passivate Shell Surface Treatment Specification: Qq-p-35 federal specification single treatment response **Shell Material Specification:** Qq-s-763 cl 302 federal specification single material response or astm a582-75 assn standard single material response **Included Contact Quantity:** 14 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces silver **Precious Material And Weight:** 0.014 silver grains, troy **Precious Material:** Silver **Thread Series Designator:** Unef and double stub Shelf Life: Unit Of Measure: **Demilitarization:** Fiig: A039b0