Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-565-8626

Thread Class:	
2a	
Thread Direction:	
Right-hand	
Body Style:	
Straight shape, external coupling	
Overall Length:	
Between 1.172 inches and 1.222 inches	
Overall Height:	
Between 1.117 inches and 1.133 inches	
Overall Width:	
Between 1.117 inches and 1.133 inches	
Environmental Protection:	
Moisture resistant and vibration resistant and heat resistant	
Unthreaded Mounting Hole Diameter:	
Between 0.116 inches and 0.126 inches	
Center To Center Distance Between Mounting Facilities Parallel	To Height:
Between 0.901 inches and 0.911 inches	U
Distance Between Centerlines Of Mounting Facilities Parallel To	Body Width:
Between 0.901 inches and 0.911 inches	
Distance From Mounting Shoulder To Front Face:	
Between 0.765 inches and 0.775 inches	
Threaded Device Type:	
Back shell	
Mating End Quantity:	
1	
Contact Position Arrangement Style:	
Ak-9 single mating end	
Contact Removability:	
Removable single mating end single contact grouping	
Polarization Method:	
Key, multiple key groove	
Insert Position In Deg:	
280.0 and 242.0 and 130.0 and 48.0	
Shell Type:	
Solid	
Connector Locking Method:	
Bayonet pin	
Thready Qty Per Inch (tpi):	
28	
Thread Size:	
0.875 inches	

Electrical Receptacle Connector - Page 2 of 2



Terminal Location:	
Back single mating end single contact grouping	
Contact Material:	
Copper alloy single mating end single contact grouping	
Contact Surface Treatment:	
Gold single mating end single contact grouping	
Contact Surface Treatment Specification:	
Mil-g-45204, ty, 1, class 1 military specification single treatment response single mating end single contact grouping	
Terminal Type:	
Crimp single mating end single contact grouping	
Shell Material:	
Aluminum alloy 6061	
Shell Surface Treatment:	
Chromium	
Shell Material Specification:	
Qq-a-367, comp 6061, t6 federal specification single material response	
Included Contact Quantity:	
9 single mating end single contact grouping	
Included Contact Type:	
Round pin single mating end single contact grouping	
Special Features:	
Contact designation 14-09 or d03	
Precious Material And Location:	
Contact surfaces gold	
Precious Material And Weight:	
0.009 gold grains, troy	
Precious Material:	
Gold	
Test Data Document:	
81349-mil-c-81511 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in	specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on	certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Thread Series Designator:	
Un	
Specification Data:	
81349-mil-c-81511/51 government specification	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	
Mil-std (military Standard):	