Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-566-2462

7
Thread Class:
2a
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
Between 1.815 inches and 1.905 inches
Overall Diameter:
2.315 inches
Environmental Protection:
Cold resistant and shock resistant and vibration proof
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
32-7 single mating end
Contact Removability:
Nonremovable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
41.0 single mating end 1st contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end 3rd contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end 1st contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
125.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling nut
Thready Qty Per Inch (tpi):
16 and 10
Thread Size:
1.875 inches and 2.000 inches
Terminal Location:
Back single mating end all contact groupings
Contact Material:
Copper alloy single mating end all contact groupings

Electrical Plug Connector - Page 2 of 2



Contact Surface Treatment: Silver single mating end all contact groupings **Insert Material:** Rubber single mating end **Contact Surface Treatment Specification:** Qq-s-365 federal specification single treatment response single mating end all contact groupings **Terminal Type:** Solder well single mating end all contact groupings Shell Material: Aluminum alloy **Shell Surface Treatment:** Cadmium **Shell Surface Treatment Specification:** Qq-p-416, type 2 federal specification single treatment response **Included Contact Quantity:** 7 single mating end 1st contact grouping **Included Contact Type:** Round socket single mating end all contact groupings **Precious Material And Location:** Contact surfaces silver **Precious Material And Weight:** 0.035 silver grains, troy **Precious Material:** Silver **Thread Series Designator:** Un and double stub Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A039b0