NSN 5935-00-566-5662

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-566-5662 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.465 inches **Overall Height:** 1.578 inches **Overall Width:** 1.578 inches **Environmental Protection:** Moisture resistant and salt water resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.115 inches and 0.125 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** Between 1.245 inches and 1.255 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 1.245 inches and 1.255 inches **Distance From Mounting Shoulder To Front Face:** Between 0.556 inches and 0.587 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 22-55 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 600.0 single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 330.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin

Thread Length:

0.290 inches

NSN 5935-00-566-5662

Electrical Receptacle Connector - Page 2 of 2



Thread Size:
1.312 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Rubber single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
Included Contact Quantity:
55 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.055 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0