

View Online at <https://aerobasegroup.com/nsn/5935-00-568-3394>

Body Style:

Straight shape

Overall Length:

Between 3.340 inches and 3.360 inches

Overall Height:

0.565 inches

Overall Width:

Between 0.240 inches and 0.260 inches

Unthreaded Mounting Hole Diameter:

0.120 inches

Distance Between Mounting Facility Centers:

3.100 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mail-g-45204, type 1, class 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290, class 2 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping

Guide Design And Location:

D shape socket right-hand at 6 oclock

Insert Material Specification:

Mil-m-14, type sdg or mfh military specification single material response single mating end

Included Contact Quantity:

50 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.050 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

spec.