Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-568-3449

#### **Body Style:**

Angle shape, pcb type

#### **Overall Length:**

3.350 inches

## **Overall Height:**

0.359 inches

**Overall Width:** 

0.550 inches

#### **Environmental Protection:**

Vibration resistant and shock resistant and salt water resistant and humidity resistant and thermal shock resistant

## **Unthreaded Mounting Hole Diameter:**

0.120 inches

## **Distance Between Mounting Facility Centers:**

3.100 inches

#### Mating End Quantity:

1

## **Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

#### Contact Removability:

Nonremovable single mating end single contact grouping

## **Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

# **Polarization Method:**

Guide pin/socket

## **Connector Locking Method:**

Friction

## **Operating Tempurature Rating:**

Between -65.0 degrees celsius and 125.0 degrees celsius

## **Terminal Location:**

Side single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping

# **Insert Material:**

Plastic polyphenylene single mating end and glass fiber single mating end

# Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

# **Terminal Type:**

Printed circuit single mating end single contact grouping

# **Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping

# NSN 5935-00-568-3449

Electrical Receptacle Connector - Page 2 of 2



**Guide Design And Location:** D shape socket left-hand top at 12 oclock Included Contact Quantity: 50 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.050 gold grains, troy **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.