## NSN 5935-00-570-5868

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-570-5868

**Body Style:** Straight shape **Overall Length:** Between 2.620 inches and 2.650 inches **Overall Height:** 0.660 inches **Overall Width:** Between 0.590 inches and 0.620 inches **Unthreaded Mounting Hole Diameter:** Between 0.115 inches and 0.125 inches **Distance Between Mounting Facility Centers:** Between 2.401 inches and 2.411 inches **Mating End Quantity: Contact Position Arrangement Style:** 50 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Steel **Shell Surface Treatment:** Cadmium and chromate

**Insert Material Specification:** 

Mil-p-19833, type gdi-30f military specification single material response single mating end

**Included Contact Quantity:** 

50 single mating end single contact grouping

## NSN 5935-00-570-5868

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type
-----------------------

Round pin single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:** 

0.050 gold grains, troy and 0.050 silver grains, troy

**Precious Material:** 

Gold and silver

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-p-19833 spec.