

View Online at <https://aerobasegroup.com/nsn/5935-00-574-3695>

Body Style:

Straight shape, flush mount

Overall Height:

3.938 inches

Overall Width:

3.375 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.000 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

2.875 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

2

Contact Position Arrangement Style:

81 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

13.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

2950.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

4100.0 single mating end single contact grouping

Polarization Method:

Polarization boss

Shell Type:

Solid

Connector Locking Method:

Jackscrew-socket

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Crimp and solder single mating end single contact grouping

Shell Material:

Aluminum alloy

Insert Material Specification:

MI-m-14, type sdc-f military specification single material response single mating end

Included Contact Quantity:

162 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.162 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

spec.