Electrical Receptacle Connector - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5935-00-576-6970

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
1.465 inches
Overall Height:
1.578 inches
Overall Width:
1.578 inches
Environmental Protection:
Moisture proof and salt water resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
Between 0.115 inches and 0.125 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 1.245 inches and 1.255 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 1.245 inches and 1.255 inches
Distance From Mounting Shoulder To Front Face:
Between 0.556 inches and 0.587 inches
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
22-55 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
600.0 single mating end single contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
142.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Thread Length:
0.290 inches

## NSN 5935-00-576-6970

Electrical Receptacle Connector - Page 2 of 2



1.312 inc	ches
-	I Location:
	gle mating end single contact grouping
	Material:
	alloy single mating end single contact grouping
••	Surface Treatment:
	gle mating end single contact grouping
Insert M	
	single mating end
Termina	
	ngle mating end single contact grouping
Shell Ma	
Aluminur	
	Irface Treatment:
Cadmiun	
	rface Treatment Specification:
	<ol> <li>type 2, cl 3 federal specification single treatment response</li> </ol>
	I Contact Quantity:
	e mating end single contact grouping
-	I Contact Type:
	in single mating end single contact grouping
-	s Material And Location:
Contact	surfaces gold
	s Material And Weight:
	ld grains, troy
0	s Material:
Gold	
Thread S	Series Designator:
Unef	
Shelf Lif	e:
N/a	
Unit Of I	Measure:
Demilita	rization:
No	
Fiig:	
A039b0	