Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-576-7014

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
1.405 inches
Overall Height:
1.141 inches
Overall Width:
1.141 inches
Environmental Protection:
Moisture proof and salt water resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
Between 0.115 inches and 0.125 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 0.901 inches and 0.911 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 0.901 inches and 0.911 inches
Distance From Mounting Shoulder To Front Face:
Between 0.431 inches and 0.462 inches
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
14-18 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
600.0 single mating end single contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
345.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Thread Length:
0.290 inches

## NSN 5935-00-576-7014

Electrical Receptacle Connector - Page 2 of 2



υ.	875 inches
-	erminal Location:
	ack single mating end single contact grouping
	ontact Material:
С	opper alloy single mating end single contact grouping
	ontact Surface Treatment:
G	old single mating end single contact grouping
In	sert Material:
R۱	ubber single mating end
	erminal Type:
С	rimp single mating end single contact grouping
Sł	nell Material:
AI	uminum alloy
Sł	nell Surface Treatment:
Са	admium
Sł	nell Surface Treatment Specification:
Q	q-p-416, type 2, cl 3 federal specification single treatment response
In	cluded Contact Quantity:
18	3 single mating end single contact grouping
In	cluded Contact Type:
R	ound socket single mating end single contact grouping
Pr	recious Material And Location:
С	ontact surfaces gold
Pr	recious Material And Weight:
0.	018 gold grains, troy
Pr	recious Material:
G	old
Tł	nread Series Designator:
Uı	nef
Sł	helf Life:
N/	'a
Uı	nit Of Measure:
De	emilitarization:
No	0
Fi	ig: