

View Online at <https://aerobasegroup.com/nsn/5935-00-577-0022>

Thread Direction:

Right-hand

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.813 inches

Overall Height:

0.984 inches

Overall Width:

1.094 inches

Body Length:

1.094 inches

Environmental Protection:

Pressure proof and vibration resistant and watertight

Unthreaded Mounting Hole Diameter:

0.150 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.813 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

22.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

150.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

200.0 single mating end single contact grouping

Connector Locking Method:

Externally threaded shell

Thread Size:

0.750 inches

Insert Material:

Plastic single mating end

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Anodize

Included Contact Quantity:

2 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

1 insert rotated 145.0 deg. Ccw from normal position and 1 satin primer and o.D. Enamel on flange top and edges

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0