

View Online at <https://aerobasegroup.com/nsn/5935-00-577-0287>

Body Style:

Straight shape w/clamp

Overall Diameter:

1.327 inches

Cable Entrance Diameter:

Between 0.296 inches and 0.562 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

"3, 5-15" single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

15.0 single mating end 2nd contact grouping

Contact Maximum Ac Voltage Rating In Volts:

125.0 single mating end 2nd contact grouping

Contact Maximum Dc Voltage Rating In Volts:

125.0 single mating end 2nd contact grouping

Polarization Method:

Contact

Connector Cable Strain Relief Method:

Cable clamp

Terminal Location:

Back single mating end all contact groupings

Terminal Type:

Screw single mating end all contact groupings

Included Contact Quantity:

2 single mating end 2nd contact grouping

Included Contact Type:

U-socket single mating end 1st contact grouping

Test Data Document:

81348-wc596 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-wc596 government specification

Specification Or Standard:

D41 style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0