

View Online at <https://aerobasegroup.com/nsn/5935-00-577-0288>

Body Style:

Straight shape w/clamp

Mating End Quantity:

1

Contact Position Arrangement Style:

"3, 6-15, 6-30" single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

15.0 single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

250.0 single mating end all contact groupings

Contact Maximum Dc Voltage Rating In Volts:

250.0 single mating end all contact groupings

Polarization Method:

Contact to contact polarizing keys

Insert Position In Deg:

0.0

Shell Type:

Hood, top opening

Connector Locking Method:

Bayonet pin

Connector Cable Strain Relief Method:

Cable clamp

Terminal Location:

Front single mating end all contact groupings

Contact Surface Treatment:

Copper single mating end all contact groupings

Terminal Type:

Screw single mating end all contact groupings

Shell Material:

Plastic

Included Contact Quantity:

2 single mating end 2nd contact grouping

Test Data Document:

81348-w-c-596 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81348-w-c-596 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0