

View Online at <https://aerobasegroup.com/nsn/5935-00-577-0295>

**Body Material:**

Plastic

**Body Style:**

Top mount w/metal saddle

**Fabrication Method:**

Molded

**Overall Length:**

Between 0.734 inches and 0.766 inches

**Overall Height:**

0.578 inches

**Overall Width:**

Between 0.469 inches and 0.500 inches

**Mounting Hole Diameter:**

Between 0.091 inches and 0.101 inches

**Body Mounting Hole Accommodation Diameter:**

Between 0.438 inches and 0.469 inches

**Distance Between Mounting Facility Centers:**

Between 0.557 inches and 0.567 inches

**Mounting Hole Style:**

Round, w/two mounting holes

**Specific Equipment Accommodated:**

Electron tube

**Contact Maximum Current Rating In Amps:**

1.0

**Contact Material:**

Beryllium copper

**Contact Surface Treatment:**

Silver

**Accommodated Contact Quantity:**

8

**Component Shield Mounting Method:**

Bayonet

**Saddle Material:**

Brass

**Saddle Surface Treatment:**

Nickel

**Projection Length Below Mounting Surface:**

0.328 inches

**Mounting Method:**

Saddle

**Mounting Type For Which Designed:**

Chassis

**Features Provided:**

Center shield and component retaining device

**Contact Position Arrangement Style:**

Subminiature

**Contact Maximum Voltage In Volts And Current Type:**

500.0 ac and 500.0 dc

**Special Features:**

Rated 100 degrees c continuous operating temp

**Precious Material And Location:**

Contact surfaces silver

**Precious Material And Weight:**

0.008 silver grains, troy

**Precious Material:**

Silver

**Test Data Document:**

96906-ms35407 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

8 tab, solder lug

**Specification Data:**

96906-ms35407 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A02300