

View Online at <https://aerobasegroup.com/nsn/5935-00-577-0295>

Body Material:

Plastic

Body Style:

Top mount w/metal saddle

Fabrication Method:

Molded

Overall Length:

Between 0.734 inches and 0.766 inches

Overall Height:

0.578 inches

Overall Width:

Between 0.469 inches and 0.500 inches

Mounting Hole Diameter:

Between 0.091 inches and 0.101 inches

Body Mounting Hole Accommodation Diameter:

Between 0.438 inches and 0.469 inches

Distance Between Mounting Facility Centers:

Between 0.557 inches and 0.567 inches

Mounting Hole Style:

Round, w/two mounting holes

Specific Equipment Accommodated:

Electron tube

Contact Maximum Current Rating In Amps:

1.0

Contact Material:

Beryllium copper

Contact Surface Treatment:

Silver

Accommodated Contact Quantity:

8

Component Shield Mounting Method:

Bayonet

Saddle Material:

Brass

Saddle Surface Treatment:

Nickel

Projection Length Below Mounting Surface:

0.328 inches

Mounting Method:

Saddle

Mounting Type For Which Designed:

Chassis

Features Provided:

Center shield and component retaining device

Contact Position Arrangement Style:

Subminiature

Contact Maximum Voltage In Volts And Current Type:

500.0 ac and 500.0 dc

Special Features:

Rated 100 degrees c continuous operating temp

Precious Material And Location:

Contact surfaces silver

Precious Material And Weight:

0.008 silver grains, troy

Precious Material:

Silver

Test Data Document:

96906-ms35407 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

8 tab, solder lug

Specification Data:

96906-ms35407 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A02300