

View Online at <https://aerobasegroup.com/nsn/5935-00-577-1943>

**Body Style:**

Straight shape, thru-hole mount, external coupling

**Overall Diameter:**

1.188 inches

**Distance From Mounting Shoulder To Front Face:**

0.656 inches

**Mounting Facility Thickness:**

0.125 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

1912p single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

25.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

2000.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

2500.0 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet pin

**Connector Cable Strain Relief Method:**

Potting type

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

**Insert Material:**

Rubber single mating end

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium and chromate

**Included Contact Quantity:**

12 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surf gold and contact surf silver

**Precious Material:**

Gold and silver

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0