## NSN 5935-00-577-2524

Plug-in Electronic Components Socket - Page 1 of 2



| Body Material: Plastic                            |
|---|
|   |
|   |
| Thread Class:                                     |
| 2a  |
| Thread Direction:                                 |
| Right-hand  |
| Body Style:                                       |
| Top mount w/studs                                 |
| Fabrication Method:                               |
| Molded  |
| Overall Length:                                   |
| 1.138 inches                                      |
| Overall Height:                                   |
| 0.785 inches                                      |
| Mounting Hole Diameter:                           |
| 0.170 inches                                      |
| <b>Body Mounting Hole Accommodation Diameter:</b> |
| 1.031 inches                                      |
| Distance Between Mounting Facility Centers:       |
| 1.406 inches                                      |
| Mounting Hole Style:                              |
| Round, w/two mounting holes                       |
| Specific Equipment Accommodated:                  |
| Relay   |
| Contact Maximum Current Rating In Amps:           |
| 7.5   |
| Contact Material:                                 |
| Phosphor bronze                                   |
| Contact Surface Treatment:                        |
| Gold and silver                                   |
| Accommodated Contact Quantity:                    |
| 20  |
| Polarization Type:                                |
| Contact position                                  |
| Projection Length Below Mounting Surface:         |
| 0.300 inches                                      |
| Mounting Method:                                  |
| Threaded stud                                     |
| Mounting Type For Which Designed:                 |
| Chassis   |

Features Provided:

Component retaining device

NSN 5935-00-577-2524 Plug-in Electronic Components Socket - Page 2 of 2



| Гhready Qty Per Inch (tpi):                           |
|---|
| 32  |
| Thread Size:  |
| 0.138 inches  |
| Contact Position Arrangement Style:                   |
| Concentric  |
| Precious Material And Location:                       |
| Contact surfaces gold and contact surfaces silver     |
| Precious Material And Weight:                         |
| 0.020 gold grains, troy and 0.020 silver grains, troy |
| Precious Material:                                    |
| Gold and silver                                       |
| Thread Series Designator:                             |
| Jnc   |
| Terminal Type And Quantity:                           |
| 20 tab, solder lug                                    |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:                                      |
| <del>-</del>  |
| Demilitarization:                                     |
| No  |
| Fiig:   |
| A02300  |