## NSN 5935-00-577-2700

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-577-2700 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.938 inches **Overall Height:** Between 1.969 inches and 2.031 inches **Overall Width:** Between 1.969 inches and 2.031 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.142 inches and 0.157 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 1.557 inches and 1.567 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 1.557 inches and 1.567 inches **Distance From Mounting Shoulder To Front Face:** Between 0.812 inches and 0.843 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 28-20 single mating end **Contact Removability:** Removable single mating end all contact groupings **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end all contact groupings **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end all contact groupings **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type:

Solid

**Connector Locking Method:** 

Externally threaded shell

## NSN 5935-00-577-2700

Electrical Receptacle Connector - Page 2 of 2



| Thread Length:                                      |
|---|
| 0.625 inches  |
| Thready Qty Per Inch (tpi):                         |
| 18  |
| Thread Size:  |
| 1.750 inches  |
| Terminal Location:                                  |
| Back single mating end all contact groupings        |
| Contact Surface Treatment:                          |
| Silver single mating end all contact groupings      |
| Terminal Type:                                      |
| Solder well single mating end all contact groupings |
| Shell Material:                                     |
| Aluminum alloy                                      |
| Shell Surface Treatment:                            |
| Cadmium   |
| Included Contact Quantity:                          |
| 4 single mating end 1st contact grouping            |
| Bushing Accommodation Hole Shape:                   |
| Round   |
| Included Contact Type:                              |
| Round pin single mating end all contact groupings   |
| Precious Material And Location:                     |
| Contact surfaces silver                             |
| Precious Material And Weight:                       |
| 0.030 silver grains, troy                           |
| Precious Material:                                  |
| Silver  |
| Thread Series Designator:                           |
| Uns   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:                                    |
|   |
| Demilitarization:                                   |
| No  |
| Fiig:   |
| A039b0  |
|   |