Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-577-8715

## **Body Style:** Straight shape **Overall Length:** Between 2.714 inches and 2.744 inches **Overall Height:** 0.615 inches **Overall Width:** Between 0.479 inches and 0.509 inches **Environmental Protection:** Heat resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.086 inches **Distance Between Mounting Facility Centers:** 2.500 inches Mating End Quantity: 1 **Contact Position Arrangement Style:** 37 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 350.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 490.0 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Plastic polyamide single mating end **Terminal Type:** Solder well single mating end single contact grouping **Contact Material Specification:**

Qq-b-626, comp 360 federal specification single material response single mating end single contact grouping



Shell Material:
Steel comp 1017
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification single treatment response
Shell Material Specification:
Qq-s-636 federal specification single material response
Insert Material Specification:
Mil-p-17091b military specification single material response single mating end
Included Contact Quantity:
37 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.037 gold grains, troy and 0.037 silver grains, troy
Precious Material:
Gold and silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-p-17091b spec.