# NSN 5935-00-578-0239

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-578-0239 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.938 inches **Overall Height:** 1.281 inches **Overall Width:** 1.281 inches **Unthreaded Mounting Hole Diameter:** 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.969 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.969 inches **Distance From Mounting Shoulder To Front Face:** 0.562 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 16s-8 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 22.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Shell Type:** Solid **Connector Locking Method:** Externally threaded shell **Thread Size:** 1.000 inches

**Terminal Location:** 

Back single mating end single contact grouping

# NSN 5935-00-578-0239

Electrical Receptacle Connector - Page 2 of 2



#### **Contact Surface Treatment:**

Gold single mating end single contact grouping and copper single mating end single contact grouping

#### **Insert Material:**

Plastic diallyl phthalate single mating end

## **Contact Surface Treatment Specification:**

Mil-c-14550, cl 4 military specification 1st treatment response single mating end single contact grouping and mil-g-45204, type 2, class 2 military specification 2nd treatment response single mating end single contact grouping

## **Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:** 

Aluminum alloy

#### **Shell Surface Treatment:**

Cadmium and chromate

#### **Insert Material Specification:**

Mil-m-14, ty mdg military specification single material response single mating end

# **Included Contact Quantity:**

5 single mating end single contact grouping

### **Included Contact Type:**

Round pin single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces silver

# **Precious Material And Weight:**

0.005 silver grains, troy

Precious Material:

Silver

**Thread Series Designator:** 

Unef

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No Fiig:

4 0001

A039b0

## Mil-std (military Standard):

Mil-c-14550 spec.