Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-578-3159

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Height:
1.688 inches
Overall Width:
1.688 inches
Unthreaded Mounting Hole Diameter:
0.169 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.282 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.282 inches
Distance From Mounting Shoulder To Front Face:
0.438 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
Sk-d12 single mating end
Contact Removability:
Nonremovable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
30.0 single mating end 1st contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thready Qty Per Inch (tpi):
6
Thread Size:
1.312 inches
Terminal Location:
Back single mating end all contact groupings

## NSN 5935-00-578-3159

Electrical Receptacle Connector - Page 2 of 2



Copper all	oy single mating end all contact groupings
Contact S	urface Treatment:
Silver sing	le mating end all contact groupings
Insert Mat	erial:
Plastic me	lamine single mating end or plastic phenolic single mating end
Terminal 1	Гуре:
Solder wel	I single mating end all contact groupings
Shell Mate	erial:
Aluminum	alloy
Shell Surf	ace Treatment:
Cadmium	
Included (	Contact Quantity:
8 single ma	ating end 2nd contact grouping
Included (	Contact Type:
Round pin	single mating end all contact groupings
Precious I	Material And Location:
Contact su	rfaces silver
Precious I	Material And Weight:
0.012 silve	r grains, troy
Precious I	Material:
Silver	
Thread Se	ries Designator:
Special ac	me
Shelf Life:	
N/a	
Unit Of Me	easure:
Demilitaria	zation:
No	
Fiig:	
A039b0	