## NSN 5935-00-579-1224

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-579-1224

**Body Style:** Straight shape, flush mount **Overall Length:** 1.061 inches **Overall Height:** 2.000 inches **Overall Width:** 2.012 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 1.432 inches and 1.442 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 1.715 inches and 1.725 inches **Distance From Mounting Shoulder To Front Face:** 0.936 inches **Mating End Quantity: Contact Position Arrangement Style:** 26 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 13.0 single mating end single contact grouping Shell Type: Solid **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Plastic melamine single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium

**Included Contact Quantity:** 

26 single mating end single contact grouping

**Included Contact Type:** 

Round socket single mating end single contact grouping

## NSN 5935-00-579-1224

Electrical Receptacle Connector - Page 2 of 2



Special Features:
Polarized at position 08
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
$0.026 \ \text{gold grains}, \ \text{troy} \ \text{and} \ 0.026 \ \text{silver grains}, \ \text{troy}$
Precious Material:
Gold and silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0