Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-579-1424

Body Style: Straight shape Overall Length: 0.954 inches Overall Height: 2.047 inches Overall Witht: 2.000 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 1.715 inches and 1.725 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 1.432 inches and 1.442 inches Between 1.432 inches and 1.442 inches 7.66 inches Mating End Quantity: 7 7.766 inches Pontact Rostition Arrangement Style: 67 single mating end Contact Removability: Removable single mating end single contact grouping Polarization Method: 1 polarization post Shell Type: Sold Tortact Material: Quartition post Contact Surface Treatment: Sold Single mating end single contact grouping Contact Material: Quartition post Sold Single mating end single contact grouping and single contac	View Online at https://aerobasegroup.com/nsn/5935-00-579-1424
Overall Leight: 0.954 inches Overall Height: 2.047 inches Overall Width: 2.000 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 1.715 inches and 1.725 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 1.432 inches and 1.442 inches Distance From Mounting Shoulder To Front Face: 0.766 inches Mating End Quantity: 1 Contact Position Arrangement Style: 57 single mating end Contact Removability: Removable single mating end single contact grouping Polarization Method: 1 polarization method: 1 polarization method: 2 otnact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: 1 polarization post Shell Type: Solid Contact Material: Copper alloy single mating end single contact grouping and silver single mating end single contact grouping Contact Material: Gold single mating end single contact grouping and silver single mating end single contact grouping Contact Materia!	Body Style:
0.954 indes Overall Height: 2.047 inches Overall Width: 2.000 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 1.715 inches and 1.725 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 1.432 inches and 1.442 inches Distance From Mounting Shoulder To Front Face: 0.766 inches Mating End Quantity: 1 Contact Position Arrangement Style: 57 single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximu Current Rating In Amps: 7.5 single mating end single contact grouping Polarization post Shell Type: Sold Contact Surige mating end single contact grouping Contact Material: Coper alloy single mating end single contact grouping Contact Surface Treatment: Cold single mating end single contact grouping Contact Surface Treatment: Cold single mating end single contact grouping and silver single mating end single contact grouping Bater inelen ensing en ating end single contact grouping and silver single ma	Straight shape
Overall Height: 2.047 inches Overall Width: 2.000 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 1.715 inches and 1.725 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 1.432 inches and 1.442 inches Distance From Mounting Shoulder To Front Face: 0.766 inches Mating End Quantity: 1 Contact Position Arrangement Style: 57 single mating end Contact Removability: Removabile single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: 1 polarization post Shell Type: Solid Terminal Location: Contact Material: Coper alloy single mating end single contact grouping Contact Surface Treatment: Cold single mating end single contact grouping and silver single mating end single contact grouping Contact Material: Cottact Material: Cottact Material: Cottact Surface Treatment: Cottact Material: </th <th>Overall Length:</th>	Overall Length:
2.047 index 2.000 inches 2.000	0.954 inches
Overall With: 2.000 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 1.715 inches and 1.725 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Widht: Between 1.432 inches and 1.442 inches Distance From Mounting Shoulder To Front Face: 0.766 inches Mating End Quantity: 1 Contact Position Arrangement Style: 57 single mating end Contact Removability: Removable single mating end single contact grouping Contact Removability: Removable single mating end single contact grouping Parization Method: 1 polarization post Shell Type: Solid Terminal Location: Back single mating end single contact grouping Contact Material: Coper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping and silver single mating end single contact grouping Contact Material: Plastic melamine single mating end single contact grouping Contact Material: Plastin melamine single mating end single contact grouping <th>Overall Height:</th>	Overall Height:
2.000 inches 2.000 inches 2.000 inches 2.000 inches 4.000 inches 4.000 inches 5.000 inches and 1.725 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 1.432 inches and 1.442 inches Distance From Mounting Shoulder To Front Face: 0.766 inches 4.000 inches 4.000 inches 4.000 inches 4.000 inches 4.000 inches 5.7 single mating End Quantity: 1. 5.7 single mating end 5.7 single mating end single contact grouping 5.000 inches 5.000 inches 5.0000 inches 5.000 i	2.047 inches
Center Octerer Distance Between Mounting Facilities Parallel To Height: Between 1.715 inches and 1.725 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 1.432 inches and 1.442 inches Distance From Mounting Shoulder To Front Face: 0.766 inches Mating End Quantity: 1 Contact Position Arrangement Style: 57 single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: 1 polarization post Shell Type: Solid Contact Material: Copper alloy single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Material: Gold single mating end single contact grouping Insert Material: Polarization post Shell complemating end single contact grouping and silver single mating end single contact grouping Contact Material: Gold single mating end single contact grouping and silver single mating end single contact grouping in the polarizat	Overall Width:
Between 1.715 inches and 1.725 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 1.432 inches and 1.442 inches Distance From Mounting Shoulder To Front Face: 0.766 inches Mating End Quantity: 1 Contact Position Arrangement Style: 57 single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: 1 polarization post Shell Type: Solid Contact Material: Copper alloy single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Material: Gold single mating end single contact grouping Contact Surface Treatment: Plastic melamine single mating end Insert Material: Polarization Shell Surface Treatment: Plastic melamine single contact grouping and silver single mating end single contact grouping in the polarization polarization polarization polarization polarization polarization polarization polarization polarization polari	2.000 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 1.432 inches and 1.442 inches Distance From Mounting Shoulder To Front Face: 0.766 inches Mating End Quantity: 1 Contact Position Arrangement Style: 57 single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: 1 polarization post Shell Type: Solid Terminal Location: Back single mating end single contact grouping Contact Surface Treatment: Cold single mating end single contact grouping Contact Surface Treatment: Plastic melamine single contact grouping and silver single mating end single contact grouping Contact Surface Treatment: Plastic melamine single contact grouping and silver single mating end single contact grouping Cirter Material: Plastic melamine single contact grouping and silver single mating end single contact grouping Cirter Material: Plastic melamine single contact grouping and silver single mating end single contact grouping <	Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 1.432 inches and 1.442 inches Distance From Mounting Shoulder To Front Face: 0.766 inches Mating End Quantity: 1 Contact Position Arrangement Style: 57 single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: 1 polarization post Shell Type: Solid Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping and silver single mating end single contact grouping Insert Material: Polatic melamine single contact grouping and silver single mating end single contact grouping Insert Material: Polatic melamine single contact grouping and silver single mating end single contact grouping Insert Material: Polatic melamine single mating end Insert Material: Auminum alloy Shell Material: Auminum alloy	Between 1.715 inches and 1.725 inches
Distance From Mounting Shoulder To Front Face: 0.766 inches Mating End Quantity: 1 Contact Position Arrangement Style: 57 single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: 1 polarization post Shell Type: Solid Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Plastic melamine single contact grouping and silver single mating end single contact grouping Terminal Location: Back single mating end single contact grouping Contact Surface Treatment: Plastic melamine single mating end Shell Material: Plastic melamine single mating end Shell Material: Auminum alloy Shell Surface Treatment: Cadmium and chromate	Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.766 inches Mating End Quantity: 1 Contact Position Arrangement Style: 57 single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: 1 polarization post Shell Type: Solid Terminal Location: Back single mating end single contact grouping Contact Material: Contact Surface Treatment: Gold single mating end single contact grouping and silver single mating end single contact grouping Insert Material: Plastic melamine single contact grouping and silver single mating end single contact grouping Contact Surface Treatment: Plastic melamine single contact grouping and silver single mating end single contact grouping Cirimp single mating end single contact grouping and silver single mating end single contact grouping Cirimp single mating end single contact grouping Cirimp single mating end single contact grouping Solid Terminal Type: Cirimp single mating end single contact grouping Shell Material: <tr< td=""><td>Between 1.432 inches and 1.442 inches</td></tr<>	Between 1.432 inches and 1.442 inches
Mating End Quantity: 1 Contact Position Arrangement Style: 57 single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: 1 polarization post Shell Type: Solid Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping and silver single mating end single contact grouping Insert Material: Polatic mating end single contact grouping and silver single mating end single contact grouping Insert Material: Polatic malamine single mating end Terminal Type: Crimp single mating end single contact grouping Material: Plastic melamine single mating end Terminal Type: Crimp single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment: Cadmium and chromate	Distance From Mounting Shoulder To Front Face:
1 Contact Position Arrangement Style: 57 single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: 1 polarization post Shell Type: Solid Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping and silver single mating end single contact grouping Insert Material: Plastic melamine single mating end Plastic melamine single mating end Terminal Type: Cothact Surface Treatment: Plastic melamine single mating end Terminal Type: Crimp single mating end single contact grouping Material: Plastic melamine single mating end Shell Material: Aluminum alloy Shell Surface Treatment: Cadmium and chromate	0.766 inches
Contact Position Arrangement Style: 57 single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: 1 polarization post Shell Type: Solid Terminal Location: Back single mating end single contact grouping Contact Material: Contact Surface Treatment: Gold single mating end single contact grouping and silver single mating end single contact grouping Insert Material: Plastic melamine single mating end Freminal Type: Cimps mating end single contact grouping and silver single mating end single contact grouping Insert Material: Plastic melamine single mating end Insert Material: Aluminum alloy Shell Surface Treatment: Aluminum alloy Chell Surface Treatment: Codmium and chromate	Mating End Quantity:
57 single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: 1 polarization post Shell Type: Solid Terminal Location: Back single mating end single contact grouping Contact Material: Cosper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping and silver single mating end single contact grouping Insert Material: Plastic melamine single mating end Insert Material: Cimp single mating end single contact grouping and silver single mating end single contact grouping Material: Plastic melamine single mating end Shell Material: Aluminum alloy Shell Surface Treatment: Cadmium and chromate	1
Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: 1 polarization post Shell Type: Solid Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping and silver single mating end single contact grouping Insert Material: Plastic melamine single mating end Terminal Type: Cimp single mating end single contact grouping and silver single mating end single contact grouping Herting Insert Material: Plastic melamine single mating end Ferminal Type: Cimp single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment: Cidmium alloy	Contact Position Arrangement Style:
Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: 1 polarization post Shell Type: Solid Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping and silver single mating end single contact grouping Insert Material: Plastic melamine single mating end Piastic melamine single contact grouping Cirrinal Type: Ciring single mating end single contact grouping Ferminal Type: Plastic melamine single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment: Aluminum alloy Shell Surface Treatment: Contact Treatment: Contact Grouping and chromate	57 single mating end
Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: 1 polarization post Shell Type: Solid Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping and silver single mating end single contact grouping Insert Material: Plastic melamine single mating end Terminal Type: Crimp single mating end single contact grouping Shell Material: Plastic melamine single mating end Terminal Type: Crimp single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment: Cadmium and chromate	Contact Removability:
7.5 single mating end single contact grouping Polarization Method: 1 polarization post Shell Type: Solid Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping and silver single mating end single contact grouping Insert Material: Plastic melamine single mating end Terminal Type: Crimp single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment: Cadmium and chromate	Removable single mating end single contact grouping
Polarization Method: 1 polarization post Shell Type: Solid Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping and silver single mating end single contact grouping Insert Material: Plastic melamine single mating end Terminal Type: Crimp single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment: Cadmium and chromate	Contact Maximum Current Rating In Amps:
1 polarization post Shell Type: Solid Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping and silver single mating end single contact grouping Insert Material: Plastic melamine single mating end Terminal Type: Crimp single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment: Cadmium and chromate	7.5 single mating end single contact grouping
Shell Type:SolidTerminal Location:Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingContact Surface Treatment:Gold single mating end single contact grouping and silver single mating end single contact groupingInsert Material:Plastic melamine single mating endTerminal Type:Crimp single mating end single contact groupingShell Material:Aluminum alloyShell Surface Treatment:Cadmium and chromate	Polarization Method:
Solid Ferminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping and silver single mating end single contact grouping Insert Material: Plastic melamine single mating end Ferminal Type: Crimp single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment: Cadmium and chromate	1 polarization post
Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping and silver single mating end single contact grouping Insert Material: Plastic melamine single mating end Terminal Type: Crimp single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment: Cadmium and chromate	Shell Type:
Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingContact Surface Treatment:Gold single mating end single contact grouping and silver single mating end single contact groupingInsert Material:Plastic melamine single mating endTerminal Type:Crimp single mating end single contact groupingShell Material:Aluminum alloyShell Surface Treatment:Cadmium and chromate	Solid
Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping and silver single mating end single contact grouping Insert Material: Plastic melamine single mating end Terminal Type: Crimp single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment: Cadmium and chromate	Terminal Location:
Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping and silver single mating end single contact grouping Insert Material: Plastic melamine single mating end Terminal Type: Crimp single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment: Cadmium and chromate	Back single mating end single contact grouping
Contact Surface Treatment: Gold single mating end single contact grouping and silver single mating end single contact grouping Insert Material: Plastic melamine single mating end Terminal Type: Crimp single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment: Cadmium and chromate	Contact Material:
Gold single mating end single contact grouping and silver single mating end single contact grouping Insert Material: Plastic melamine single mating end Terminal Type: Crimp single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment: Cadmium and chromate	Copper alloy single mating end single contact grouping
Insert Material: Plastic melamine single mating end Terminal Type: Crimp single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment: Cadmium and chromate	Contact Surface Treatment:
Plastic melamine single mating end Terminal Type: Crimp single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment: Cadmium and chromate	Gold single mating end single contact grouping and silver single mating end single contact grouping
Terminal Type: Crimp single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment: Cadmium and chromate	Insert Material:
Crimp single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment: Cadmium and chromate	Plastic melamine single mating end
Shell Material: Aluminum alloy Shell Surface Treatment: Cadmium and chromate	Terminal Type:
Aluminum alloy Shell Surface Treatment: Cadmium and chromate	Crimp single mating end single contact grouping
Shell Surface Treatment: Cadmium and chromate	Shell Material:
Cadmium and chromate	Aluminum alloy
	Shell Surface Treatment:
Included Contact Quantity:	Cadmium and chromate
	Included Contact Quantity:

57 single mating end single contact grouping



Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

Polarized at position 03

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.057 gold grains, troy and 0.057 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0