

View Online at <https://aerobasegroup.com/nsn/5935-00-581-4292>

Thread Class:

2a and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape threaded

Overall Length:

1.531 inches

Overall Diameter:

Between 1.865 inches and 1.885 inches

Distance From Mounting Shoulder To Front Face:

Between 1.146 inches and 1.166 inches

Mounting Facility Thickness:

0.235 inches

Threaded Device Type:

Coupling facility and mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

22-18 single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

13.0 single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

900.0 single mating end 2nd contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end 1st contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thready Qty Per Inch (tpi):

18 and 18

Thread Size:

1.375 inches and 1.375 inches

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Silver single mating end all contact groupings

Insert Material:

Rubber single mating end

Terminal Type:

Solder well single mating end all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Silver

Included Contact Quantity:

8 single mating end 2nd contact grouping

Included Contact Type:

Round socket single mating end all contact groupings

Precious Material And Location:

Contact surfaces and shell surface silver

Precious Material And Weight:

0.011 silver grains, troy and 0.011 silver grains, troy

Precious Material:

Silver

Thread Series Designator:

Unef and unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0