Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-581-4872

Thread	Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape

Overall Length:

2.000 inches

Overall Height:

0.859 inches

Overall Width:

0.750 inches

Environmental Protection:

Vibration resistant

Unthreaded Mounting Hole Diameter:

0.128 inches

Distance Between Mounting Facility Centers:

1.687 inches

Threaded Device Type:

Mounting stud

Mating End Quantity:

1

Contact Position Arrangement Style:

34 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Thread Length:

0.266 inches

Thready Qty Per Inch (tpi):

40

Thread Size:

0.112 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold and silver single mating end single contact grouping

NSN 5935-00-581-4872

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Plastic melamine mineral filled single mating end
Terminal Type:
Solder well single mating end single contact grouping
Unable To Decode:
Unable to decode and unable to decode
Included Contact Quantity:
34 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.034 gold grains, troy and 0.034 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0