## NSN 5935-00-581-5730

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-581-5730

**Body Style:** 

Straight shape

**Overall Length:** 

Between 2.073 inches and 2.103 inches

**Overall Height:** 

0.663 inches

**Overall Width:** 

Between 0.479 inches and 0.509 inches

**Environmental Protection:** 

Moisture resistant and salt water resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:** 

Between 0.115 inches and 0.125 inches

**Distance Between Mounting Facility Centers:** 

Between 1.847 inches and 1.857 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

9w4 single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

5.0 single mating end single contact grouping

**Polarization Method:** 

Mating end

Shell Type:

Solid

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold and copper single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate single mating end

**Terminal Type:** 

Solder well single mating end single contact grouping

**Shell Material:** 

Steel

**Shell Surface Treatment:** 

Cadmium and chromate

**Insert Material Specification:** 

Mil-m-19833, type gdi-30f military specification single material response single mating end

## NSN 5935-00-581-5730

Electrical Receptacle Connector - Page 2 of 2



## **Included Contact Quantity:** 5 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.005 gold grains, troy **Precious Material:** Gold Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.