Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-581-6406

Thread Class:
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
1.465 inches
Overall Height:
1.703 inches
Overall Width:
1.703 inches
Environmental Protection:
Moisture proof and vibration resistant and salt water resistant
Unthreaded Mounting Hole Diameter:
Between 0.142 inches and 0.152 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 1.370 inches and 1.380 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 1.370 inches and 1.380 inches
Distance From Mounting Shoulder To Front Face:
Between 0.589 inches and 0.620 inches
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
24-61 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
600.0 single mating end single contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
270.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Thread Length:
0.290 inches

NSN 5935-00-581-6406

Electrical Receptacle Connector - Page 2 of 2



Thread S	
1.438 inch	
	Location:
-	le mating end single contact grouping
Contact N	
Copper al	loy single mating end single contact grouping
Contact S	Surface Treatment:
Gold singl	le mating end single contact grouping
Insert Ma	iterial:
Rubber si	ngle mating end
Terminal	Туре:
Crimp sing	gle mating end single contact grouping
Shell Mat	erial:
Aluminum	alloy
Shell Sur	face Treatment:
Cadmium	
Shell Sur	face Treatment Specification:
Qq-p-416	, type 2, cl 3 federal specification single treatment response
Included	Contact Quantity:
61 single	mating end single contact grouping
Included	Contact Type:
Round so	cket single mating end single contact grouping
Precious	Material And Location:
Contact s	urfaces gold
Precious	Material And Weight:
0.061 gold	d grains, troy
Precious	Material:
Gold	
Thread S	eries Designator:
Unef	
Shelf Life	
N/a	
Unit Of M	leasure:
Demilitar	ization:
No	
Fiig:	
A039b0	