

View Online at <https://aerobasegroup.com/nsn/5935-00-581-6593>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Environmental Protection:**

Moisture proof

**Threaded Device Type:**

Mounting hole

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

13 single mating end

**Contact Removability:**

Nonremovable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:**

5.0 single mating end all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

875.0 single mating end 2nd contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

1400.0 single mating end 1st contact grouping

**Polarization Method:**

Mating end

**Shell Type:**

Solid

**Connector Cable Strain Relief Method:**

Cable clamp

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.112 inches

**Terminal Location:**

Back single mating end all contact groupings

**Insert Material:**

Plastic single mating end

**Terminal Type:**

Solder well single mating end all contact groupings

**Shell Material:**

Aluminum alloy

**Included Contact Quantity:**

2 single mating end 2nd contact grouping

**Included Contact Type:**

Round socket single mating end 1st contact grouping

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0