

View Online at <https://aerobasegroup.com/nsn/5935-00-581-6593>

Thread Class:

2b

Thread Direction:

Right-hand

Environmental Protection:

Moisture proof

Threaded Device Type:

Mounting hole

Mating End Quantity:

1

Contact Position Arrangement Style:

13 single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

5.0 single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

875.0 single mating end 2nd contact grouping

Contact Maximum Dc Voltage Rating In Volts:

1400.0 single mating end 1st contact grouping

Polarization Method:

Mating end

Shell Type:

Solid

Connector Cable Strain Relief Method:

Cable clamp

Thready Qty Per Inch (tpi):

40

Thread Size:

0.112 inches

Terminal Location:

Back single mating end all contact groupings

Insert Material:

Plastic single mating end

Terminal Type:

Solder well single mating end all contact groupings

Shell Material:

Aluminum alloy

Included Contact Quantity:

2 single mating end 2nd contact grouping

Included Contact Type:

Round socket single mating end 1st contact grouping

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0