## NSN 5935-00-581-6627

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-581-6627

**Body Style:** 

Straight edge type w/mounting flange

**Overall Length:** 

4.598 inches

**Overall Height:** 

0.692 inches

**Overall Width:** 

0.340 inches

**Environmental Protection:** 

Heat resistant

**Unthreaded Mounting Hole Diameter:** 

0.142 inches

**Distance Between Mounting Facility Centers:** 

4.344 inches

**Board Accommodated Length:** 

3.911 inches single board

**Board Accommodated Width:** 

0.063 inches

**Mating End Quantity:** 

**Contact Position Arrangement Style:** 

2 rows of independent contacts inserted board single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

5.0 single mating end single contact grouping

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate single mating end

**Terminal Type:** 

Solder well single mating end single contact grouping

**Insert Material Specification:** 

Mil-m-14, type sdg-f military specification single material response single mating end

**Included Contact Quantity:** 

48 single mating end single contact grouping

**Included Contact Type:** 

Bifurcated spring single mating end single contact grouping

## NSN 5935-00-581-6627

Electrical Receptacle Connector - Page 2 of 2



<b>Precious Material And Location:</b>
Contact surfaces gold
Precious Material And Weight:
0.048 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-m-14 spec.