

View Online at <https://aerobasegroup.com/nsn/5935-00-581-6941>

**Body Material:**

Ceramic

**Body Style:**

Crystal, top or bottom mount

**Fabrication Method:**

Molded

**Body Surface Treatment:**

Glazed

**Overall Length:**

Between 0.843 inches and 0.875 inches

**Temperature Rating:**

200.0 degrees celsius

**Overall Height:**

Between 0.656 inches and 0.688 inches

**Overall Width:**

0.375 inches

**Mounting Hole Diameter:**

Between 0.120 inches and 0.130 inches

**Mounting Hole Style:**

Single mounting hole/slot

**Contact Resistance In Ohms:**

0.015

**Specific Equipment Accommodated:**

Crystal

**Contact Maximum Current Rating In Amps:**

1.0

**Contact Material:**

Beryllium copper

**Contact Surface Treatment:**

Gold and copper

**Accommodated Contact Quantity:**

2

**Projection Length Below Mounting Surface:**

Between 0.343 inches and 0.375 inches

**Mounting Method:**

Body through hole

**Mounting Type For Which Designed:**

Chassis

**Contact Position Arrangement Style:**

In line

**Contact Maximum Voltage In Volts And Current Type:**

500.0 ac and 500.0 dc

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.002 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-s-12883 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 tab, solder lug

**Specification Data:**

81349-mil-s-12883/4 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A02300