

View Online at <https://aerobasegroup.com/nsn/5935-00-581-6941>

Body Material:

Ceramic

Body Style:

Crystal, top or bottom mount

Fabrication Method:

Molded

Body Surface Treatment:

Glazed

Overall Length:

Between 0.843 inches and 0.875 inches

Temperature Rating:

200.0 degrees celsius

Overall Height:

Between 0.656 inches and 0.688 inches

Overall Width:

0.375 inches

Mounting Hole Diameter:

Between 0.120 inches and 0.130 inches

Mounting Hole Style:

Single mounting hole/slot

Contact Resistance In Ohms:

0.015

Specific Equipment Accommodated:

Crystal

Contact Maximum Current Rating In Amps:

1.0

Contact Material:

Beryllium copper

Contact Surface Treatment:

Gold and copper

Accommodated Contact Quantity:

2

Projection Length Below Mounting Surface:

Between 0.343 inches and 0.375 inches

Mounting Method:

Body through hole

Mounting Type For Which Designed:

Chassis

Contact Position Arrangement Style:

In line

Contact Maximum Voltage In Volts And Current Type:

500.0 ac and 500.0 dc

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.002 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-s-12883 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 tab, solder lug

Specification Data:

81349-mil-s-12883/4 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A02300