

View Online at <https://aerobasegroup.com/nsn/5935-00-581-8822>

Thread Class:

2a

Body Style:

Straight shape, internal coupling

Overall Length:

1.420 inches

Overall Diameter:

1.531 inches

Environmental Protection:

Pressure proof and humidity resistant and shock proof and vibration resistant

Threaded Device Type:

Back shell

Mating End Quantity:

1

Contact Removability:

Removable single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

600.0 single mating end all contact groupings

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

216.0

Shell Type:

Solid

Connector Locking Method:

Bayonet latch

Thread Length:

0.290 inches

Thread Size:

1.188 inches

Shell Material:

Aluminum alloy

Shell Material Specification:

Qq-a-367 federal specification single material response

Included Contact Quantity:

37 single mating end 2nd contact grouping

Test Data Document:

81349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-c-26482 spec.