## NSN 5935-00-583-1630

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-583-1630 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling w/strain relief **Body Length:** 1.547 inches **Overall Diameter:** 0.688 inches **Cable Entrance Diameter:** 0.219 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Removability:** Nonremovable single mating end single contact grouping **Shell Type:** Solid **Connector Locking Method:** Externally threaded shell **Connector Cable Strain Relief Method:** Cable clamp Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.688 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic single mating end **Contact Surface Treatment Specification:** Mil-g-45204 military specification single treatment response single mating end single contact grouping **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** 

Steel

## NSN 5935-00-583-1630

Electrical Plug Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium and chromate
Included Contact Quantity:
6 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.030 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):

Mil-g-45204 spec.