NSN 5935-00-583-2268

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-583-2268 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.875 inches **Bushing Diameter:** 0.750 inches **Overall Height:** 1.187 inches **Overall Width:** 1.187 inches **Unthreaded Mounting Hole Diameter:** 0.125 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.906 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.906 inches **Distance From Mounting Shoulder To Front Face:** 0.562 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 20 **Thread Size:** 0.750 inches **Terminal Location:** Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

NSN 5935-00-583-2268

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment:
Silver single mating end single contact grouping
Insert Material:
Plastic single mating end
Terminal Type:
Tab, solder lug single mating end single contact grouping
Shell Material:
Copper alloy
Shell Surface Treatment:
Silver
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial socket single mating end single contact grouping
Precious Material And Location:
Contact shell surface silver
Precious Material And Weight:
0.105 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0