NSN 5935-00-583-2901

Electrical Receptacle Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-00-583-2901



Thread Class: 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape threaded **Overall Length:** 1.406 inches **Overall Diameter:** 1.750 inches **Distance From Mounting Shoulder To Front Face:** 0.562 inches **Mounting Facility Thickness:** 0.062 inches **Threaded Device Type:** Coupling facility and mounting bushing **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 28-18 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell Thread Length: 0.500 inches and 0.312 inches Thready Qty Per Inch (tpi): 18 and 18 **Thread Size:** 0.750 inches and 1.625 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Steel single mating end single contact grouping **Contact Surface Treatment:**

Silver single mating end single contact grouping

NSN 5935-00-583-2901

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Glass and metal single mating end
Contact Surface Treatment Specification:
Qq-s-365 federal specification single treatment response single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Steel
Shell Surface Treatment:
Anodize
Included Contact Quantity:
12 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Furnished items - sealing ring
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.012 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Uns and unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0