## NSN 5935-00-583-5669

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-583-5669 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 3.090 inches **Overall Height:** 1.140 inches **Overall Width:** 0.625 inches **Distance Between Mounting Facility Centers: 2.718 inches Threaded Device Type:** Mounting stud **Mating End Quantity:** 1 **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Guide pin/socket **Connector Locking Method:** Friction Thready Qty Per Inch (tpi): Thread Size: 0.138 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate and glass fiber single mating end **Contact Surface Treatment Specification:** Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Terminal Type:** 

Turret single mating end single contact grouping

## NSN 5935-00-583-5669

Electrical Receptacle Connector - Page 2 of 2



## **Insert Material Specification:**

Mil-p-19833, type gdi-30 military specification all material responses single mating end

**Unable To Decode:** 

Unable to decode and unable to decode

**Included Contact Quantity:** 

20 single mating end single contact grouping

**Included Contact Type:** 

Round pin single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.020 gold grains, troy

**Precious Material:** 

Gold

**Thread Series Designator:** 

Unc

**Shelf Life:** 

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.