NSN 5935-00-583-8045

Thread Class:

2a

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-583-8045

Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
1.000 inches
Overall Diameter:
0.625 inches
Environmental Protection:
Waterproof and hermetic
Mounting Facility Thickness:
0.125 inches
Threaded Device Type:
Mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
Dm single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0 and 180.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Thready Qty Per Inch (tpi):
28
Thread Size:
0.438 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Silver single mating end single contact grouping and gold single mating end single contact grouping
Insert Material:
Plastic single mating end

NSN 5935-00-583-8045

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Tab, solder lug single mating end single contact grouping
Shell Material:
Steel
Included Contact Quantity:
1 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Coaxial pin single mating end single contact grouping
Precious Material And Location:
Contact surface silver and contact surface gold
Precious Material And Weight:
0.005 silver grains, troy and 0.005 gold grains, troy
Precious Material:
Silver and gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0