NSN 5935-00-583-8291

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-583-8291 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, round **Overall Length:** 0.866 inches **Overall Diameter:** 1.397 inches **Environmental Protection:** Shock resistant **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** 18-23 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 60.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin Thready Qty Per Inch (tpi): 24 **Thread Size: Terminal Location:**

1.125 inches

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Insert Material:

Plastic tetrafluoroethylene single mating end

NSN 5935-00-583-8291

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
10 single mating end single contact grouping
Included Contact Type:
Round button single mating end single contact grouping
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0