Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-586-7104

Thread Class:
2a and 2a
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape threaded
Overall Length:
Between 1.039 inches and 1.149 inches
Overall Diameter:
Between 1.490 inches and 1.510 inches
Environmental Protection:
Dust resistant and moisture resistant
Distance From Mounting Shoulder To Front Face:
Between 0.896 inches and 0.916 inches
Mounting Facility Thickness:
Between 0.094 inches and 0.200 inches
Threaded Device Type:
Coupling facility and mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
16s-1 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
13.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thready Qty Per Inch (tpi):
10 and 18
Thread Size:
1.000 inches and 1.125 inches

Electrical Receptacle Connector - Page 2 of 2



Terminal Location: Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Terminal Type:** Solder well single mating end single contact grouping Shell Material: Aluminum **Included Contact Quantity:** 7 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.007 gold grains, troy and 0.007 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Uns and unef Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0