AeroBase Group

View Online at https://aerobasegroup.com/nsn/5935-00-586-7113

Thread Class:
2a and 2a
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape threaded
Overall Length:
1.531 inches
Overall Diameter:
Between 1.740 inches and 1.760 inches
Environmental Protection:
Dust resistant and moisture resistant and vibration resistant
Distance From Mounting Shoulder To Front Face:
Between 1.146 inches and 1.166 inches
Mounting Facility Thickness:
Between 0.094 inches and 0.250 inches
Threaded Device Type:
Coupling facility and mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
18-1 single mating end
Contact Removability:
Nonremovable all mating ends all contact groupings
Contact Maximum Current Rating In Amps:
13.0 all mating ends all contact groupings
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end 1st contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end 1st contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thready Qty Per Inch (tpi):
10 and 18
Thread Size:
1.125 inches and 1.250 inches



Terminal Location: Back all mating ends all contact groupings **Contact Material:** Copper alloy all mating ends all contact groupings **Contact Surface Treatment:** Silver all mating ends all contact groupings **Insert Material:** Rubber single mating end **Terminal Type:** Solder well all mating ends all contact groupings Shell Material: Aluminum **Included Contact Quantity:** 6 single mating end 2nd contact grouping **Included Contact Type:** Round pin all mating ends all contact groupings **Precious Material And Location:** Contact surfaces silver **Precious Material And Weight:** 0.010 silver grains, troy **Precious Material:** Silver **Thread Series Designator:** Uns and unef Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0