Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-586-7148

Thread Class:
2a and 2a
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape threaded
Overall Length:
1.531 inches
Overall Diameter:
Between 1.990 inches and 2.010 inches
Environmental Protection:
Explosion proof and salt water resistant and watertight
Distance From Mounting Shoulder To Front Face:
Between 1.146 inches and 1.166 inches
Mounting Facility Thickness:
Between 0.094 inches and 0.250 inches
Threaded Device Type:
Coupling facility and mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
22-14 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
13.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thready Qty Per Inch (tpi):
10 and 18
Thread Size:
1.375 inches and 1.500 inches



Terminal Location:	
Back single mating end single contact grouping	
Contact Material:	
Copper alloy single mating end single contact grouping	ng
Contact Surface Treatment:	
Silver single mating end single contact grouping	
Insert Material:	
Rubber single mating end	
Terminal Type:	
Solder well single mating end single contact grouping	I
Shell Material:	
Aluminum alloy	
Shell Surface Treatment:	
Anodize	
Included Contact Quantity:	
19 single mating end single contact grouping	
Bushing Accommodation Hole Shape:	
Round keyed	
Included Contact Type:	
Round socket single mating end single contact group	ing
Precious Material And Location:	
Contact surfaces silver	
Precious Material And Weight:	
0.019 silver grains, troy	
Precious Material:	
Silver	
Thread Series Designator:	
Double stub and unef	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	