## NSN 5935-00-586-7153

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-586-7153 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape threaded **Overall Length:** 1.531 inches **Overall Diameter:** Between 2.115 inches and 2.135 inches **Environmental Protection:** Explosion proof and salt water resistant and watertight **Distance From Mounting Shoulder To Front Face:** Between 1.209 inches and 1.229 inches **Mounting Facility Thickness:** Between 0.094 inches and 0.312 inches **Threaded Device Type:** Coupling facility and mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** 24-28 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 13.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 200.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 250.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 **Shell Type:** Solid **Connector Locking Method:** Externally threaded shell

Thready Qty Per Inch (tpi):

10 and 16

**Thread Size:** 

1.500 inches and 1.625 inches

## NSN 5935-00-586-7153

Electrical Receptacle Connector - Page 2 of 2



Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Silver single mating end single contact grouping
Insert Material:
Rubber single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Included Contact Quantity:
24 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round keyed
Included Contact Type:
Round socket single mating end single contact grouping
Tround 300ket single mating ond single contact grouping
Precious Material And Location:
Precious Material And Location:
Precious Material And Location: Contact surfaces silver
Precious Material And Location: Contact surfaces silver Precious Material And Weight:
Precious Material And Location: Contact surfaces silver Precious Material And Weight: 0.024 silver grains, troy
Precious Material And Location: Contact surfaces silver Precious Material And Weight: 0.024 silver grains, troy Precious Material:
Precious Material And Location: Contact surfaces silver Precious Material And Weight: 0.024 silver grains, troy Precious Material: Silver
Precious Material And Location: Contact surfaces silver Precious Material And Weight: 0.024 silver grains, troy Precious Material: Silver Thread Series Designator:
Precious Material And Location: Contact surfaces silver Precious Material And Weight: 0.024 silver grains, troy Precious Material: Silver Thread Series Designator: Double stub and un
Precious Material And Location: Contact surfaces silver Precious Material And Weight: 0.024 silver grains, troy Precious Material: Silver Thread Series Designator: Double stub and un Shelf Life:
Precious Material And Location: Contact surfaces silver Precious Material And Weight: 0.024 silver grains, troy Precious Material: Silver Thread Series Designator: Double stub and un Shelf Life: N/a
Precious Material And Location: Contact surfaces silver Precious Material And Weight: 0.024 silver grains, troy Precious Material: Silver Thread Series Designator: Double stub and un Shelf Life: N/a
Precious Material And Location: Contact surfaces silver Precious Material And Weight: 0.024 silver grains, troy Precious Material: Silver Thread Series Designator: Double stub and un Shelf Life: N/a Unit Of Measure:
Precious Material And Location: Contact surfaces silver Precious Material And Weight: 0.024 silver grains, troy Precious Material: Silver Thread Series Designator: Double stub and un Shelf Life: N/a Unit Of Measure: Demilitarization: