

View Online at <https://aerobasegroup.com/nsn/5935-00-587-1318>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape threaded

Overall Length:

Between 1.433 inches and 1.443 inches

Overall Diameter:

1.871 inches

Environmental Protection:

Shock resistant and vibration resistant

Distance From Mounting Shoulder To Front Face:

1.031 inches

Threaded Device Type:

Mounting bushing

Mating End Quantity:

1

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

338.0

Shell Type:

Solid

Connector Locking Method:

Friction

Thready Qty Per Inch (tpi):

28

Thread Size:

0.437 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Wire loop single mating end single contact grouping

Shell Surface Treatment:

Anodize

Included Contact Quantity:

28 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.028 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

FiiG:

A039b0