## NSN 5935-00-589-0044

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-589-0044 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight edge type w/mounting flange **Overall Length:** 4.500 inches **Overall Height:** 0.755 inches **Overall Width:** Between 0.333 inches and 0.353 inches **Environmental Protection:** Moisture resistant and salt water resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.112 inches **Distance Between Mounting Facility Centers:** Between 4.032 inches and 4.040 inches **Board Accommodated Length:** 3.588 inches single board and 3.604 inches single board **Threaded Device Type:** Mounting hole **Board Accommodated Width:** Between 0.054 inches and 0.071 inches **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 2 rows of independent contacts inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Contact to contact polarizing keys

**Thread Length:** 0.250 inches

**Thread Size:** 

0.112 inches

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and copper single mating end single contact grouping

## NSN 5935-00-589-0044

A039b0

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Tab, solder lug single mating end single contact grouping
Included Contact Quantity:
44 single mating end single contact grouping
Included Contact Type:
Leaf spring single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.044 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-21097 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unc
Specification Data:
81349-mil-c-21097/21 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: