# NSN 5935-00-589-0251

Thread Class: 2a and 2b

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-589-0251

Thread Direction:
Right-hand and right-hand
Body Style:
Hood, side opening w/clamp
Overall Length:
2.182 inches
Overall Height:
1.715 inches
Overall Width:
Between 0.484 inches and 0.516 inches
Environmental Protection:
Shock resistant and vibration resistant
Cable Entrance Diameter:
0.220 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
20 20-20 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Polarization Method:
Jackscrew
Shell Type:
Hood, side opening
Connector Locking Method:
Jackscrew-socket
Connector Cable Strain Relief Method:
Cable clamp
Thread Length:
0.417 inches and 0.320 inches
Thread Size:
0.138 inches and 0.138 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:

Copper alloy single mating end single contact grouping

## NSN 5935-00-589-0251

Electrical Plug Connector - Page 2 of 2



#### **Contact Surface Treatment:**

Gold single mating end single contact grouping

#### **Insert Material:**

Plastic diallyl phthalate single mating end

## **Contact Surface Treatment Specification:**

Mil-g-45204, type 1 military specification single treatment response single mating end single contact grouping

### **Terminal Type:**

Solder well single mating end single contact grouping

#### **Shell Material:**

Aluminum alloy 5052

#### **Shell Surface Treatment:**

Anodize

### **Shell Surface Treatment Specification:**

Mil-a-8625, type 1 military specification single treatment response

#### **Shell Material Specification:**

Qq-a-250/8, alloy 5052, h 32 federal specification single material response

## **Insert Material Specification:**

Mil-m-14, type sdg-f military specification single material response single mating end or mil-m-19833, type gdi-30f military specification single material response single mating end

### **Included Contact Quantity:**

20 single mating end single contact grouping

## **Included Contact Type:**

Round pin single mating end single contact grouping

## **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.020 gold grains, troy

## **Precious Material:**

Gold

#### **Test Data Document:**

81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Thread Series Designator:**

Unc and unc

## **Specification Data:**

81349-mil-c-28748/5 government specification

## Shelf Life:

N/a

## **Unit Of Measure:**

## **Demilitarization:**

No

## Fiig:

A039b0