## NSN 5935-00-590-2206



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-590-2206 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape threaded **Overall Length:** 1.531 inches **Overall Diameter:** Between 1.490 inches and 1.510 inches **Environmental Protection:** Explosion proof and salt water resistant and watertight **Distance From Mounting Shoulder To Front Face:** Between 1.178 inches and 1.198 inches **Mounting Facility Thickness:** 

Between 0.094 inches and 0.282 inches

**Threaded Device Type:** 

Coupling facility and mounting bushing

**Mating End Quantity:** 

**Contact Position Arrangement Style:** 

17-59 single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

23.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:** 

500.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:** 

700.0 single mating end single contact grouping

**Polarization Method:** 

Keyway or multiple keyway

**Insert Position In Deg:** 

0.0

**Shell Type:** 

Solid

**Connector Locking Method:** 

Externally threaded shell

Thready Qty Per Inch (tpi):

10 and 18

**Thread Size:** 

1.000 inches and 1.125 inches

## NSN 5935-00-590-2206

Electrical Receptacle Connector - Page 2 of 2



| Terminal Location:                                     |
|--|
| Back single mating end single contact grouping         |
| Contact Material:                                      |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment:                             |
| Silver single mating end single contact grouping       |
| Insert Material:                                       |
| Rubber single mating end                               |
| Terminal Type:   |
| Solder well single mating end single contact grouping  |
| Shell Material:  |
| Aluminum alloy   |
| Shell Surface Treatment:                               |
| Anodize  |
| Included Contact Quantity:                             |
| 4 single mating end single contact grouping            |
| Bushing Accommodation Hole Shape:                      |
| Round keyed  |
| Included Contact Type:                                 |
| Round socket single mating end single contact grouping |
| Precious Material And Location:                        |
| Contact surfaces silver                                |
| Precious Material And Weight:                          |
| 0.004 silver grains, troy                              |
| Precious Material:                                     |
| Silver   |
| Thread Series Designator:                              |
| Double stub and unef                                   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:                                       |
|  |
| Demilitarization:                                      |
| No   |
| Fiig:  |
| A039b0   |