NSN 5935-00-590-2230

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-590-2230 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Bushing Diameter:** 1.250 inches **Environmental Protection:** Salt water resistant **Unthreaded Mounting Hole Diameter:** Between 0.143 inches and 0.147 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.530 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.530 inches **Distance From Mounting Shoulder To Front Face:** 1.127 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Externally threaded shell **Thread Size:** 1.250 inches **Terminal Location:** Back single mating end single contact grouping **Insert Material:** Plastic single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Aluminum alloy

Anodize

Shell Surface Treatment:

NSN 5935-00-590-2230

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment Specification:

Mil-a-8625, type 1 military specification single treatment response

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial socket single mating end single contact grouping

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-a-8625 spec.