

NSN 5935-00-592-0871 Electrical Plug Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-592-0871 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** 0.766 inches **Overall Diameter:** 0.859 inches **Environmental Protection:** Moisture resistant and vibration resistant and salt water resistant **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 16-10 all mating ends **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** 

Bayonet latch

**End Application:** 

Strategic weapon systems

**Thread Length:** 

0.219 inches

Thready Qty Per Inch (tpi):

24

**Thread Size:** 

0.542 inches

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and silver single mating end single contact grouping

## **NSN 5935-00-592-0871**Electrical Plug Connector - Page 2 of 2



Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Nickel
Included Contact Quantity:
13 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.013 gold grains, troy and 0.013 silver grains, troy
Precious Material:
Gold and silver
Test Data Document:
81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Uns
Specification Data:
81349-mil-c-38999 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0